

FOUNDATION

CONTRACT CARPET CUSHION

Engineered for Double-Glue & Stretch-In Installations


SE

CUSHION ATTRIBUTES


STYLE ▶	FSE270 – 6' x 45' roll
DESCRIPTION ▶	FOUNDATION SE 0.250" gauge, 12 lbs. / ft. ³ density.
MATERIAL ▶	Frothed polyurethane – a visco-elastic “memory foam” material.
THICKNESS ▶	0.250"
BOTTOM FABRIC ▶	RELEASE releasable woven backing for ease of removal at the end of useful life.
DURABILITY ▶	Compression Set 7% max. Indentation Load Deflection (25%) 14 lbs. / ft. ² Indentation Load Deflection (65%) 78.00 lbs. / ft. ²
FIRE RATING ▶	NBS Smoke Chamber <100 max. Pill Test (FF 1-70) Pass
SOUND RATING ▶	Impact Insulation Class (ASTM E492-90) 75 IIC
INSULATION RATING ▶	R-Factor (ASTM C 518) 0.87 Excellent for radiant heated floors.
WATER RESISTANCE ▶	British Spill Test Method E Pass Breathable Integral Skin Barrier, allows vapor to pass while blocking liquid spills, making clean-up easier and more effective.
ROLL SPECIFICATIONS ▶	6' x 45' roll, 270 sq. ft., 30 sq. yd. (88 lbs.)
WARRANTY ▶	Double-glue – Warranted term equal to that of co-installed carpet warranty. Stretch-in – Warranted for two carpet installations.

NOTE: Specification values subject to a 7% manufacturing tolerance.

PRODUCT SPEC



6' X 45' ROLL



14"
ROLL DIAMETER
CORE SIZE: 3.625"

GREEN PROPERTIES

RENEWABLE CONTENT ▶	Made in part with eco-friendly soybean oil, lessening dependence on petrochemicals. This reduces global warming emissions and the need for foreign oil while supporting local farmers and local producers <i>Applicable towards LEED Credit MR 6 – Rapidly Renewable Resources.</i>
INDOOR AIR QUALITY ▶	CRI Green Label certified. The only carpet cushion GREENGUARD Indoor Air Quality Certified® as a low emitting interior building material. <i>Applicable towards LEED Credit EQ 4.3 – Low Emitting Product.</i>
ANTIMICROBIAL ▶	Ultra-Fresh® Antimicrobial prevents mold, mildew and bacterial growth while controlling dust mites for life-long odor free installation.
RECYCLABLE ▶	Zero-Landfill Manufacturing waste, all materials are reused in products with recycled content. Post consumer recyclable, a valued commodity as recycled foam in the manufacturing of rebond padding.

