

**4 ROLL JOB PACK (SKU: OC400B)**

|                       |   |
|-----------------------|---|
| Box Quantity          | 4 Rolls Per Box, 400ft <sup>2</sup> (37.2m <sup>2</sup> )                   |
| Roll Size             | 3' x 33'4" Roll, 100ft <sup>2</sup> (0.9m x 10.2m Roll, 9.3m <sup>2</sup> ) |
| Roll Weight           | 12lbs (5.4kg)   |
| 4 Roll Box Dimensions | 37.5"H x 12"W x 12"L (1m x 0.3m x 0.3m)                                     |
| 4 Roll Box Weight     | 49lbs (22.2kg)  |




**72 ROLL DISTRIBUTOR PALLET (SKU: OC72009)**

|                           |   |
|---------------------------|---|
| Palletized Box Quantity   | 72 Rolls Per Palletized Box, 7,200ft <sup>2</sup> (668.9m <sup>2</sup> )    |
| Roll Size                 | 3' x 33'4" Roll, 100ft <sup>2</sup> (0.9m x 10.2m Roll, 9.3m <sup>2</sup> ) |
| Roll Weight               | 12lbs (5.4kg)   |
| Palletized Box Dimensions | 49"H x 48"W x 40"L (1.2m x 122m x 1m)                                       |
| Palletized Box Weight     | 910lbs (412.8kg)  |



**MASTER ROLL (SKU: OC3600R)**

|                 |  |
|-----------------|--|
| Roll Dimensions | 6' X 600', 3,600ft <sup>2</sup> (334.5m <sup>2</sup> ) |
| Roll Weight     | 432lbs (196kg)   |



**PRODUCT SPECIFICATIONS†**

|  |   |
|--|---|
| Material Composition                           | Frothed Polyurethane Foam   |
| Thickness (ASTM D3574)                         | 0.055" (1.4mm)  |
| Density (ASTM D3574)                           | 25lbs/ft <sup>3</sup> (400.5kg/m <sup>3</sup> )                           |
| Compression Set (ASTM D3574)                   | 5% max  |
| Tensile Strength (ASTM D3574)                  | 100lbs/ft <sup>2</sup> (488.2kg/m <sup>2</sup> )                          |
| Indentation Load Deflection - 25% (ASTM D3574) | 32lbs/ft <sup>2</sup> (156.2kg/m <sup>2</sup> )                           |
| Indentation Load Deflection - 65% (ASTM D3574) | 200+lbs/ft <sup>2</sup> (976.5+kg/m <sup>2</sup> )                        |
| NBS Smoke Density (ASTM E662)                  | <100 max  |
| Flammability Test (DOC FF 1-70)                | Pass  |
| Thermal Transmission R-Value (ASTM C518)       | 0.08 °F ft <sup>2</sup> h/Btu (Excellent for Radiant Heated Floors)       |
| Water Vapor Transmission                       | For Installations Requiring Moisture Protection Use OmniChoice Vapor Bloc |
| Antimicrobial Protection                       | Ultra-Fresh® Antimicrobial Protection                                     |
| Indoor Air Quality                             | UL GREENGUARD® GOLD Certified for Low Chemical Emissions - UL2818         |
| Installation Method                            | Approved for Floating, Nail-Down, Glue-Down, and Thin-Set Installation    |
| Warranty                                       | Warranted for Equal Term to that of the Primary Floor Covering            |

**SOUND RATING††**

|                                     |        |
|-------------------------------------|--------|
| Laminate & Wood Floors (ASTM E492)  | 71 IIC |
| Laminate & Wood Floors (ASTM E413)  | 67 STC |
| Luxury Vinyl Tile (LVT) (ASTM E492) | 73 IIC |
| Luxury Vinyl Tile (LVT) (ASTM E413) | 67 STC |
| Ceramic Tile (ASTM E492)            | 51 IIC |
| Ceramic Tile (ASTM E413)            | 54 STC |

**SUSTAINABILITY & RECYCLABILITY**

|                             |  |
|-----------------------------|--|
| Renewable & Natural Content | >50% (Made in Part with Soybean Oil and Other Natural Non-Petrochemical Resources) |
| Recyclability               | 100% Post-Consumer Recyclable  |
| LEED Credit IEQ 4.3         | Low-Emitting Materials-Flooring Systems  |
| LEED Credit MR 6.0          | Rapidly Renewable Materials  |
| LEED Credit MR 5.1          | 10% Extracted, Processed & Manufactured Regionally                                 |
| LEED Credit MR 5.2          | 20% Extracted, Processed & Manufactured Regionally                                 |

†Specifications are Subject to ±10% Manufacturing Tolerance.

††The Results of the Impact Insulation Class (IIC) and Sound Transmission Class (STC) are Influenced by the Complete Floor-Ceiling Construction.